

1	LIGHT SOURCE	44	..Pivotal head capability
2	.Electric light bulb (34)	45	..With pistol grip
3	..Fluorescent	46	..Beam supplementary to body axis, i.e., light rays directed in line with longitudinal axis
4	..Simulative		
5	...Candle or flame		
6	.Candle		
7	..Simulative	47	...Simulative
8	.Torch	48	...With distinct handle
9	CANDLE HOLDER	49	...Substantially circular body cross section (7)
10	.Combined with diverse article		
11	.With light modifier	50	..With distinct handle
12	.With means to penetrate support surface	51	.Combined with diverse article
13	.Plural, i.e., candelabrum, etc.	52	..With communications equipment, e.g., television, radio, etc. (8)
14	..Simulative		
15	..Asymmetrical	53	..With smokers' article
16	.Simulative	54	..With clock
17	..Animate	55	..With plant holder
18	..Humanoid	56	..With mirror, picture frame, or holder therefor
19	..Plant life		
20	.With distinct drip collector, e.g., flared cup, etc.	57	..Simulative
21	.Asymmetrical in elevation	58	..With table or cabinet
22	.Circular or oval base	59	..With fan or ventilator
23	.Element or attachment (1)	60	.Resiliently attached, or clamped
24	LIGHT FIXTURE	61	.Articulated or adjustable (9)
25	.Plural, connected series, i.e., light string	62	..Gooseneck type
26	.Receptacle mount, i.e., "night light" or screw-in type	63	..Pivotal movement
27	.Fiber optic	64	...And rectilinear
28	.Vehicle lamp or casing (2)	65	...Plural pivots, i.e., more than one axis
29	..Articulated type	66	..Rectilinear movement
30	..Pointer or arrow (3)	67	.Provision for post attachment or ground insertion (10)
31	..With letter, numeral, or sign, or with provision therefor (4)	68	..Combined with standard (11)
32	..Simulative	69	...Plural distinct light units
33	...Hand	70	..Plural radially arranged light units or provision therefor
34	..Combined with diverse article	71	..Axially offset singular light unit (12)
35	..Plural lamp or lens elements, or with provision therefor	72	.Attachable to overhead or vertical surface, i.e., ceiling or wall (13)
36	..Circular or oval lens, or with provision therefor (5)	73	..Simulative shape (14)
37	.Hand-held, body-attached or lantern type (6)	74	..Recessed within mounting surface
38	..Combined with diverse article	75	..Fluorescent tube type
39	..Body-attached	76	...Longitudinal axis parallel to support surface
40	..360 deg. lateral light dispersal	77Open grid-type modifier
41	...With distinct handle or carrying strap	78Exposed bulb
42	..Fluorescent tube type	79	...Circular tube
43	..Flexible light shaft	80	..Plural distinct light sources, or provision therefor (15)

81	...Attached to overhead surface	119	...Protective cover or cage, e.g., trouble light, etc.
82	...Horizontally disposed light socket	120	...Lens or panel type (19)
83	...Light source directly attached to ceiling mount	121	...Openwork
84	...Depending light source	122	...With refractive rib or groove, e.g., prismatic, etc.
85	..With light modifier	123Circular or oval (20)
86	...Repeating plural modifiers	124	...Circular or oval (21)
87	...Cantilevered or standoff-type support arm	125	...Simulative
88	...Attached to overhead surface	126	...Humanoid
89	...Light source enclosed between overhead and modifier	127	...Plant life
90	...Plural suspension elements from ceiling mount to modifier	128	...Chimney, globe or bowl, i.e., circumscribing or surrounding light source and being open at top and/or bottom (22)
91	...Polygonal modifier	129	...With external framework or filigree
92	..Cantilevered or standoff-type support arm	130	...Repeating or uniform pattern about point or axis (23)
93	..Freestanding fixture or standard (16)	131Curvilinear wall in elevation (24)
94	..Simulative	132Sinuous (25)
95	...Building or tower	133With radiating ribs or grooves
96	...Candle or candle holder	134With radiating ribs or grooves
97	...Vehicle or component thereof	135Frusto-conical or pyramidal
98	...Animate	136With radiating ribs or grooves
99	...Humanoid	137Cylindrical
100Plural	138	..Support or trim (26)
101	...Plant life	139	...Bezel, visor, or cover for vehicle lamp
102	..Plural distinct light sources or modifiers, or provision therefor	140	...Provision for security or adjustment
103	..Coil effect	141	...Frame, bridge, or harp (27)
104	..Fully enclosed light source	142	...Foot, mount, or surround (28)
105	..Light modifier open at top only	143	...Plural distinct light source supporting spokes or surrounds
106	..Bilaterally symmetrical only	144Three or more, e.g., spider, etc.
107	...Axially offset singular support for light source or modifier	145	...Cantilever or standoff type (29)
108	...With light modifier	146Simulative
109	...Horizontally elongated	147	...Simulative
110	..Repeating or uniform design about axis (17)	148Repeating or uniform pattern about point or axis (30)
111	...Tripartite	149	...Repeating or uniform pattern about point or axis (31)
112	..With light modifier	150Tripartite
113	..Element or attachment	151Quadripartite
114	..Liquid or gaseous fuel burner or component thereof	152	...Band, grille, or trim panel
115	...Mantle type	153	...Spindle or column (32)
116	...Wick type		
117	..Fuel reservoir		
118	..Light source cover or modifier, i.e., reflector, screen, or shade (18)		

- 154 ...Loop, pendant, or finial
- 155 ...Brace or trim arm (33)
- 156 ...Simulative

SEARCH NOTES FOR CLASS D26

- (1) For candle cup, bobèche, or similar support or surround, see subclasses 142+.
- (2) For lens or bezel see, respectively, subclasses 120+ and 139.
- (3) For hand simulation, see subclass 33.
- (4) Includes combination with license plate holder. For vehicle signal other than lamp, see D10-109.
- (5) For lens per se, see subclasses 120+.
- (6) Includes base. For lantern bracket, see subclass 138. For bulb cage, see subclass 119. For static signaling lamp, see D10-114. For table lamp, see subclasses 93+.
- (7) Includes patents showing striations, ridges, or depressions arranged around a substantially circular form.
- (8) Includes combination with phonograph.
- (9) Includes track-type light.
- (10) Attachment may be at top or bottom of fixture.
- (11) For lamp combined with distinct sign, see subclass 51. For lamp post, per se, see D25-126+. For arm, per se, see subclass 143 or 145.
- (12) For cantilevered arm, per se, see subclass 143 or 145.
- (13) Includes article that can function as a light fixture as it is shown, with only the insertion of the light source. If any other element is necessary to form the fixture, it is classified as an element in subclasses 113+. If there is doubt as to whether the disclosed article is a light fixture under this or indented subclasses, it is classified as an element under subclasses 113+.
- (14) Substantially entire article must be simulative; simulative detail not considered.
- (15) For backing plate, collar, surround, or spider, see subclasses 142+. For chandelier body, see subclasses 142+.
- (16) Includes combination of base and light source or modifier support. For subcombination, e.g., spindle, foot, modifier, etc., see subclasses 113+.
- (17) In determining symmetry in this and in indented subclasses, the harp, control knob, chains, etc., are not considered. Pattern must repeat three or more times.
- (18) For fixture backing plate, see subclasses 142+. For shade holder, see subclasses 138+. For segment panel of a shade, globe, etc., see subclass 152.
- (19) For vehicle lamp bezel, visor, or cover, see subclass 139. For catadioptric reflector, see D10-111+.
- (20) External shape only.
- (21) External shape only, visor or cover, see subclass 139.
- (22) For vehicle lamp bezel.
- (23) Pattern must repeat three or more times.
- (24) Exclusive of mount flange.
- (25) Exclusive of mount flange.
- (26) If the claimed disclosure includes a combination of a wall or ceiling mount support, etc., with a modifier or light source, e.g., socket, article is classified light fixture in subclasses 24+. For combined lamp post and modifier support, see D25-126+.
- (27) Includes mantle support.
- (28) Includes base member, per se. Includes chandelier body. Includes collar-type surround. For modifier trim band, see subclass 152.
- (29) For brace or trim arm, see subclass 155. For mount plate or support having security or adjustment provision, see subclass 140. For plural type, see subclasses 143+.
- (30) Pattern must repeat three or more times.
- (31) Pattern must repeat three or more times.
- (32) For post, see D25-126+.
- (33) For support arm, see subclasses 145+.
- (34) Includes photographic flashbulb.

